

# **FORANE ® 407A**

### 1. PRODUCT AND COMPANY IDENTIFICATION

### Company

Arkema Inc.

2000 Market Street

Philadelphia, Pennsylvania 19103

**Fluorochemicals** 

Customer Service Telephone Number: (800) 245-5858

(Monday through Friday, 8:30 AM to 5:30 PM EST)

**Emergency Information** 

**Transportation:** CHEMTREC: (800) 424-9300

(24 hrs., 7 days a week)

Medical: Rocky Mountain Poison Center: (303) 623-5716

(24 hrs., 7 days a week)

**Product Information** 

Product name: FORANE ® 407A Synonyms: FORANE ® 407A R-407A, HFC 407A

Molecular formula: CH2F2/CHF2CF3/CF3CH2F

Chemical family: Hydrofluorocarbon

Molecular weight: 86.2 g/mol Product use: Refrigerant

# 2. HAZARDS IDENTIFICATION

# **Emergency Overview**

Color: Clear - colourless

Physical state: gas

Form: Liquefied gas
Odor: Slightly ether-like

**CAUTION!** 

HIGH PRESSURE GAS.

LIQUID AND GAS UNDER PRESSURE.

OVERHEATING OR OVERPRESSURIZING MAY CAUSE GAS RELEASE OR VIOLENT CYLINDER BURSTING. MAY DECOMPOSE ON CONTACT WITH FLAMES OR EXTREMELY HOT METAL SURFACES TO PRODUCE TOXIC AND CORROSIVE PRODUCTS.

VAPOR REDUCES OXYGEN AVAILABLE FOR BREATHING AND IS HEAVIER THAN AIR.

MAY CAUSE FROSTBITE.

MAY CAUSE HEADACHE, NAUSEA, DIZZINESS, DROWSINESS, LOSS OF CONSCIOUSNESS.

MAY CAUSE EFFECTS ON:

**HEART** 

### **Potential Health Effects**

# Primary routes of exposure:

Inhalation and skin contact.

# ARKEMA

# **Material Safety Data Sheet**

# **FORANE ® 407A**

### Signs and symptoms of acute exposure:

Liquid: Rapid evaporation of the liquid may cause frostbite. Vapor: Vapor is heavier than air and can cause suffocation by reducing oxygen available for breathing. Central nervous system effects: headache, nausea, dizziness, drowsiness, loss of consciousness. Stress induced heart effects: irregular heart beat, rapid heart beat. (severity of effects depends on extent of exposure).

#### Skin:

Slightly irritating. (based on components)

### Inhalation:

Practically nontoxic. (based on components)

#### Eves:

Slightly irritating. (based on components)

### Medical conditions aggravated by overexposure:

Heart disease or compromised heart function.

### 3. COMPOSITION/INFORMATION ON INGREDIENTS

Chemical Name	CAS-No.	Wt/Wt	OSHA Hazardous
Ethane, 1,1,1,2-tetrafluoro-	811-97-2	40 %	Υ
Ethane, pentafluoro-	354-33-6	40 %	Υ
Methane, difluoro-	75-10-5	20 %	Υ

The substance(s) marked with a "Y" in the Hazard column above, are those identified as hazardous chemicals under the criteria of the OSHA Hazard Communication Standard (29 CFR 1910.1200).

This material is classified as hazardous under Federal OSHA regulation.

# 4. FIRST AID MEASURES

### Inhalation:

If inhaled, remove victim to fresh air. If not breathing, give artificial respiration. If breathing is difficult, give oxygen. Get medical attention.

### Skin:

If on skin, flush exposed skin with lukewarm water (not hot), or use other means to warm skin slowly. Get medical attention if frostbitten by liquid or if irritation occurs. Wash clothing before reuse. Thoroughly clean shoes before reuse.

### **Eyes**

Immediately flush eye(s) with plenty of water.

### Ingestion:

Ingestion is not applicable - product is a gas at ambient temperatures.

### Notes to physician:

Do not give drugs from adrenaline-ephedrine group.



# **FORANE ® 407A**

### **5. FIRE-FIGHTING MEASURES**

Flash point Not applicable

Auto-ignition temperature: not determined

Lower flammable limit (LFL): None.

Upper flammable limit (UFL): None.

### Extinguishing media (suitable):

Use extinguishing measures to suit surroundings.

### **Protective equipment:**

Fire fighters and others who may be exposed to products of combustion should wear full fire fighting turn out gear (full Bunker Gear) and self-contained breathing apparatus (pressure demand / NIOSH approved or equivalent). Fire fighting equipment should be thoroughly decontaminated after use.

### Further firefighting advice:

Keep containers cool by spraying with water if exposed to fire.

Water mist should be used to reduce vapor concentrations in air.

### Fire and explosion hazards:

May decompose on contact with flames or extremely hot metal surfaces to produce toxic and corrosive products. Liquid and gas under pressure, overheating or overpressurizing may cause gas release and/or violent cylinder bursting.

Container may explode if heated due to resulting pressure rise.

Some mixtures of HCFCs and/or HFCs, and air or oxygen may be combustible if pressurized and exposed to extreme heat or flame.

When burned, the following hazardous products of combustion can occur:

Hydrogen fluoride

# 6. ACCIDENTAL RELEASE MEASURES

### In case of spill or leak:

Use Halogen leak detector or other suitable means to locate leaks or check atmosphere. Keep upwind. Evacuate enclosed spaces and disperse gas with floor-level forced-air ventilation. Stop the leak if you can do so without risk. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits.

# ARKEMA

# **Material Safety Data Sheet**

# **FORANE ® 407A**

### 7. HANDLING AND STORAGE

### **Handling**

### General information on handling:

Avoid breathing gas.

Keep container closed.

Use only with adequate ventilation.

Do not enter confined spaces unless adequately ventilated.

Use equipment rated for cylinder pressure.

Use a backflow preventative device in piping.

Wash thoroughly after handling.

Close valve after each use and when empty.

Emptied container retains vapor and product residue.

Observe all labeled safeguards until container is cleaned, reconditioned or destroyed.

# **Storage**

### General information on storage conditions:

Store in well ventilated area away from heat and sources of ignition such as flame, sparks and static electricity.

### Storage stability - Remarks:

Do not apply direct flame to cylinder. Do not store cylinder in direct sun or expose it to heat above 120 F (48.9 C.). Do not drop or refill this cylinder.

# Storage incompatibility – General:

Keep away from oxidising agents and strongly acid or alkaline materials.

### Temperature tolerance – Do not store above:

118 °F (48 °C)

# 8. EXPOSURE CONTROLS/PERSONAL PROTECTION

# **Airborne Exposure Guidelines:**

### Ethane, 1,1,1,2-tetrafluoro- (811-97-2)

US. Workplace Environmental Exposure Level (WEEL) Guides

Time Weighted Average (TWA): 1,000 ppm (4,240 mg/m3)

Remarks: Listed

### Ethane, pentafluoro- (354-33-6)

US. Workplace Environmental Exposure Level (WEEL) Guides

Time Weighted Average (TWA): 1,000 ppm (4,900 mg/m3)

Remarks: Listed

Methane, difluoro- (75-10-5)

US. Workplace Environmental Exposure Level (WEEL) Guides



# **FORANE ® 407A**

Time Weighted Average (TWA): 1,000 ppm (2,200 mg/m3)

Remarks: Listed

Only those components with exposure limits are printed in this section. Limits with skin contact designation above have skin contact effect. Air sampling alone is insufficient to accurately quantitate exposure. Measures to prevent significant cutaneous absorption may be required. Limits with a sensitizer designation above mean that exposure to this material may cause allergic reactions.

# **Engineering controls:**

Investigate engineering techniques to reduce exposures below airborne exposure limits. Provide ventilation if necessary to control exposure levels below airborne exposure limits (see above). If practical, use local mechanical exhaust ventilation at sources of air contamination such as open process equipment.

### **Respiratory protection:**

Avoid breathing gas. Where airborne exposure is likely or airborne exposure limits are exceeded (if applicable, see above), use NIOSH approved respiratory protection equipment appropriate to the material and/or its components (full facepiece recommended). Consult respirator manufacturer to determine appropriate type equipment for a given application. Observe respirator use limitations specified by NIOSH or the manufacturer. For emergency and other conditions where there may be a potential for significant exposure or where exposure limit may be significantly exceeded, use an approved full face positive-pressure, self-contained breathing apparatus or positive-pressure airline with auxiliary self-contained air supply. Respiratory protection programs must comply with 29 CFR § 1910.134.

### Skin protection:

Wear appropriate chemical resistant protective clothing and chemical resistant gloves to prevent skin contact. Consult glove manufacturer to determine appropriate type glove material for given application. Rinse immediately if skin is contaminated. Wash contaminated clothing and clean protective equipment before reuse. Wash thoroughly after handling.

# Eye protection:

Use good industrial practice to avoid eye contact.

# 9. PHYSICAL AND CHEMICAL PROPERTIES

Color: Clear - colourless

Physical state: gas

Form: Liquefied gas

Odor: Slightly ether-like

**pH:** not applicable

**Density:** not determined

**Specific Gravity (Relative** 

density):

1.14 (77 °F( 25 °C))

Product code: 04072 Version 1.0 Issued on: 03/04/2009 Page: 5 / 12



# **FORANE ® 407A**

**Vapor pressure:** 7,839 mmHg (70.0 °F (21.1 °C))

Vapor density: 2.99 kg/m3

**Boiling point/boiling** 

range:

-44.1 °F (-42.3 °C)

Freezing point: not determined

Melting point: not determined

Solubility in water: negligible

**% Volatiles:** 100 %

Molecular weight: 86.2 g/mol

# 10. STABILITY AND REACTIVITY

### Stability:

This material is chemically stable under normal and anticipated storage, handling and processing conditions.

### Materials to avoid:

Strong oxidizing agents Strong acids Alkaline materials

### Conditions / hazards to avoid:

Heat.

### Hazardous decomposition products:

Thermal decomposition giving toxic and corrosive products: Hydrogen fluoride
Carbon monoxide
Carbon dioxide (CO2)
Carbonyl halides

# 11. TOXICOLOGICAL INFORMATION

Data on this material and/or its components are summarized below.

# Data for Ethane, 1,1,1,2-tetrafluoro- (811-97-2)

# **Acute toxicity**

### Inhalation:

Practically nontoxic. (rat) 4 h LC50 approximately 2,360 mg/l (~ 567000 ppm).

Practically nontoxic. (rat) 0.5 h LC50 approximately 3,122 mg/l (~ 750000 ppm).

Signs/effects reported after acute exposure. (mouse, dog, cat, monkey) signs: anesthetic effects

# PRKEMA

# **Material Safety Data Sheet**

# **FORANE ® 407A**

Skin Irritation:

Slightly irritating. (rabbit) (24 h)

**Eye Irritation:** 

Slightly irritating. (rabbit)

### Sensitization:

Causes cardiac sensitization. inhalation. (dog) Stress-induced heart effects. irregular heart beat, rapid heart beat, in some cases, sudden death (Reaction may occur in response to stress (natural adrenaline release) or administration of epinephrine.)

### Skin Sensitization:

Repeated skin exposure. (guinea pig) No skin allergy was observed.

### Repeated dose toxicity

Repeated inhalation administration to rat / No adverse systemic effects reported.

### Genotoxicity

### **Assessment in Vitro:**

No genetic changes were observed in laboratory tests using: bacteria, animal cells

# Genotoxicity

### Assessment in Vivo:

No genetic changes were observed in laboratory tests using: animals

### **Developmental toxicity**

Exposure during pregnancy. inhalation (rat and rabbit) / No birth defects were observed. (delays in development, at doses that produce effects in mothers)

# Data for Ethane, pentafluoro- (354-33-6)

### **Acute toxicity**

### Inhalation:

Practically nontoxic. (rat) 4 h LC50 > 3,900 mg/l (> 800000 ppm).

### Sensitization:

Causes cardiac sensitization. inhalation. (dog) Stress induced heart effects: irregular heart beat, rapid heart beat, in some cases, sudden death (Reaction may occur in response to stress (natural adrenaline release) or administration of epinephrine.)

### Repeated dose toxicity

Subchronic inhalation administration to rat / No adverse systemic effects reported.

# Genotoxicity

# Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, animal cells

# **Genotoxicity**

### Assessment in Vivo:

No genetic changes were observed in laboratory tests using: animals

# ARKEMA

# **Material Safety Data Sheet**

# **FORANE ® 407A**

### **Developmental toxicity**

Exposure during pregnancy. inhalation (rat and rabbit) / No birth defects were observed.

### Data for Methane, difluoro- (75-10-5)

### **Acute toxicity**

#### Inhalation:

Practically nontoxic. (rat) 4 h LC50 > 520000 ppm. signs: anesthetic effects, central nervous system depression

### Sensitization:

Causes cardiac sensitization. inhalation. (dog) Stress induced heart effects: irregular heart beat, rapid heart beat, in some cases, sudden death (Reaction may occur in response to stress (natural adrenaline release) or administration of epinephrine.)

### Repeated dose toxicity

Repeated inhalation administration to rat / no adverse effects

# Genotoxicity

#### Assessment in Vitro:

No genetic changes were observed in laboratory tests using: bacteria, animal cells

### Genotoxicity

### Assessment in Vivo:

No genetic changes were observed in laboratory tests using: animals

# **Developmental toxicity**

Exposure during pregnancy. inhalation (rat and rabbit) / No birth defects were observed. (at doses that produce effects in mothers)

# 12. ECOLOGICAL INFORMATION

### **Chemical Fate and Pathway**

Data on this material and/or its components are summarized below.

# Data for Ethane, 1,1,1,2-tetrafluoro- (811-97-2)

### **Biodegradation:**

Not readily biodegradable. (28 d) biodegradation 3 %

### **Bioaccumulation:**

Practically no potential to bioaccumulate.

### **Octanol Water Partition Coefficient:**

log Pow = 1.06

### Photodegradation:

Degradation in the atmosphere Half-life direct photolysis: = 9.6 - 16.7 y (in atmosphere)



# **FORANE ® 407A**

### **Global Warming Potential:**

GWP = 0.3 (Halocarbon global warming potential.)

### **Ozone Depletion Potential:**

ODP = 0

# Data for Ethane, pentafluoro- (354-33-6)

### **Biodegradation:**

Not readily biodegradable. (Closed Bottle test, 28 d) biodegradation 5 %

### **Octanol Water Partition Coefficient:**

log Pow = 1.48

# **Global Warming Potential:**

GWP 0.84 (Halocarbon global warming potential; HGWP; (R-11 = 1))

### **Ozone Depletion Potential:**

ODP < 0.001 (Ozone depletion potential; ODP; (R-11 = 1))

# Data for Methane, difluoro- (75-10-5)

### **Biodegradation:**

Not biodegradable. (28 d) biodegradation 5 % / Closed Bottle test

Slight potential to bioaccumulate.

### **Octanol Water Partition Coefficient:**

log Pow = 0.21

### **Global Warming Potential:**

GWP = 543 (CO2)

# **Ozone Depletion Potential:**

ODP = 0 (Ozone depletion potential; ODP; (R-11 = 1))

# **Ecotoxicology**

Data on this material and/or its components are summarized below.

# Data for Ethane, 1,1,1,2-tetrafluoro- (811-97-2)

# Aquatic toxicity data:

Practically nontoxic. Oncorhynchus mykiss (rainbow trout) 96 h LC50 = 450 mg/l

# Aquatic invertebrates:

Practically nontoxic. Daphnia magna (Water flea) 48 h EC50 = 930 mg/l

# Microorganisms:

Practically nontoxic. Bacteria 16 h EC10 > 730 mg/l



# **FORANE ® 407A**

### 13. DISPOSAL CONSIDERATIONS

### Waste disposal:

Do not vent the container contents, or product residuals, to the atmosphere. Recover and reclaim unused contents or residuals as appropriate. Recovered/reclaimed product can be returned to an approved certified reclaimer or back to the seller depending on the material. Completely emptied disposable containers can be disposed of as recyclable steel. Returnable cylinders must be returned to seller. Dispose of in accordance with federal, state and local regulations. Consult a regulatory specialist to determine appropriate state or local reporting requirements, for assistance in waste characterization and/or hazardous waste disposal and other requirements listed in pertinent environmental permits. Note: Chemical additions to, processing of, or otherwise altering this material may make this waste management information incomplete, inaccurate, or otherwise inappropriate. Furthermore, state and local waste disposal requirements may be more restrictive or otherwise different from federal laws and regulations.

### 14. TRANSPORT INFORMATION

### **US Department of Transportation (DOT)**

UN Number : 3338

Proper shipping name : Refrigerant gas R 407A

Class : 2.2 Marine pollutant : no

# International Maritime Dangerous Goods Code (IMDG)

UN Number : 3338

Proper shipping name : REFRIGERANT GAS R 407A

Class : 2.2 Marine pollutant : no

### 15. REGULATORY INFORMATION

### **Chemical Inventory Status**

EU. EINECS EINECS Conforms to

US. Toxic Substances Control Act

TSCA

The components of this product are all on

the TSCA Inventory.

Australia. Industrial Chemical (Notification and AICS Conforms to

Assessment) Act

Canada. Canadian Environmental Protection Act DSL This product contains one or several

(CEPA). Domestic Substances List (DSL). (Can. Gaz. components listed in the Canadian NDSL

Part II, Vol. 133) list. All other components are on the DSL

list.

Japan. Kashin-Hou Law List ENCS (JP) Conforms to

Korea. Toxic Chemical Control Law (TCCL) List KECI (KR) Conforms to

Philippines. The Toxic Substances and Hazardous PICCS (PH) Conforms to

and Nuclear Waste Control Act



# **FORANE ® 407A**

China. Inventory of Existing Chemical Substances IECSC (CN) Conforms to

New Zealand. Inventory of Chemicals (NZIoC), as NZIOC Conforms to

published by ERMA New Zealand

### <u>United States - Federal Regulations</u>

### SARA Title III - Section 302 Extremely Hazardous Chemicals:

The components in this product are either not SARA Section 302 regulated or regulated but present in negligible concentrations.

### SARA Title III - Section 311/312 Hazard Categories:

Acute Health Hazard, Sudden Release of Pressure Hazard

### SARA Title III - Section 313 Toxic Chemicals:

SARA 313: This material does not contain any chemical components with known CAS numbers that exceed the threshold (De Minimis) reporting levels established by SARA Title III, Section 313.

# Comprehensive Environmental Response, Compensation, and Liability Act (CERCLA) - Reportable Quantity (RQ):

The components in this product are either not CERCLA regulated, regulated but present in negligible concentrations, or regulated with no assigned reportable quantity.

### Toxic Substances Control Act – Section 12(b):

<u>Chemical Name</u> <u>CAS-No.</u> Ethane, 1,1,1,2-tetrafluoro- 811-97-2

# OSHA Regulated Carcinogens (NTP, IARC, OSHA Listed):

### NTP:

No component of this product present at levels greater than or equal to 0.1% is identified as a known or anticipated carcinogen by NTP.

### IARC

No component of this product present at levels greater than or equal to 0.1% is identified as probable, possible or confirmed human carcinogen by IARC.

### OSHA:

No component of this product present at levels greater than or equal to 0.1% is identified as a carcinogen or potential carcinogen by OSHA.

# **United States - State Regulations**

# Massachusetts Right to Know

No components are subject to the Massachusetts Right to Know Act.



# **FORANE ® 407A**

# **New Jersey Right to Know**

Chemical NameCAS-No.Methane, difluoro-75-10-5

Pennsylvania Right to Know

Chemical NameCAS-No.Ethane, 1,1,1,2-tetrafluoro-811-97-2

Ethane, pentafluoro- 354-33-6

Methane, difluoro- 75-10-5

### Pennsylvania Right to Know - Environmentally Hazardous Substance(s)

Chemical NameCAS-No.Methane, difluoro-75-10-5

### California Prop. 65

This product does not contain any chemicals known to the State of California to cause cancer, birth defects, or any other reproductive defects.

### **16. OTHER INFORMATION**

### Latest Revision(s):

Revised Section(s): Initial entry
Reference number: 000000061053
Date of Revision: 03/04/2009
Date Printed: 03/04/2009

FORANE ® is a registered trademark of Arkema Inc.

Arkema Inc. believes that the information and recommendations contained herein (including data and statements) are accurate as of the date hereof. NO WARRANTY OF FITNESS FOR ANY PARTICULAR PURPOSE, WARRANTY OF MERCHANTABILITY, OR ANY OTHER WARRANTY, EXPRESSED OR IMPLIED, IS MADE CONCERNING THE INFORMATION PROVIDED HEREIN. The information provided herein relates only to the specific product designated and may not be valid where such product is used in combination with any other materials or in any process. Further, since the conditions and methods of use are beyond the control of Arkema Inc., Arkema Inc. expressly disclaims any and all liability as to any results obtained or arising from any use of the product or reliance on such information.