

# PRODUCT PROFILE

## UL489 CIRCUIT BREAKERS

### BULLETIN 1492-MC

Rockwell Automation introduces a new line of circuit breakers approved for North American applications. The Allen-Bradley Bulletin 1492-MC is designed and manufactured to meet the requirements of UL489 and CSA 22.2 No. 5.1 to provide Branch Circuit Protection.

### VERSATILITY

UL489 Circuit Breakers provide a variety of product configurations by offering current ranges of 10A to 100A and 120/240V AC or 240V AC control. The 1492-MC DIN Rail-mounted circuit breakers are either 1/2" or 1" wide. Ground Fault Sensing versions are also available for GFCI (5mA) and GFEP (30mA) applications.


Also available for your control applications are a one (1) pole and (2) pole version rated 480Y/277 V AC for currents 15 ... 100 A.

The Ground Fault versions and the 480Y/277 versions are panel mounted and may be DIN rail mounted with a simple, snap-on adapter.

### SIMPLIFIED MAINTENANCE

Toggle position identifies the localized tripped devices so troubleshooting can be done quickly.

## BRANCH CIRCUIT PROTECTION FOR NORTH AMERICAN APPLICATIONS



### NORTH AMERICAN PRODUCT OFFERING


Designed to meet the Branch Circuit Protection Standards of the  
US - UL489 and Canadian - CSA 22.2 No. 5.1.

**ESSENTIAL COMPONENTS.  
EXCEPTIONAL VALUE.**

# SPECIFICATION OVERVIEW

<b>1492-MC Series A</b>	
Number of Poles	1, 2, and 3 poles
Specification	UL489, CSA 22.2 No.5.1 GFCI – UL 943, GFEP – UL1053
Approvals	UL Listed, CSA Certified
HACR rating	Yes
Rated Voltage	120/240 V AC, 240 V AC, 480Y/277 V AC
Rated Tripping Current At 40°C	10, 15, 20, 25, 30, 35, 40, 45, 50, 55, 60, 70, 80, 90, 100 A
Rated Interrupting Capability	10 kA 480Y/277 - 14 kA
Degree of Protection	1/2 in. wide – finger safe 1 in. wide – add terminal covers for Finger Safe
Normal Operating Environment	0°C...60°C 0 to 95% RH non-condensing

## 1492<sup>1</sup>-MC B A 2 40 T



<sup>1</sup> Important: The following catalog number breakdown is for explanation purposes only. It is NOT a product configurator. Not all combinations of fields are valid product catalog numbers.

[www.rockwellautomation.com](http://www.rockwellautomation.com)

### Power, Control and Information Solutions Headquarters

Americas: Rockwell Automation, 1201 South Second Street, Milwaukee, WI 53204-2496 USA, Tel: (1) 414.382.2000, Fax: (1) 414.382.4444

Europe/Middle East/Africa: Rockwell Automation, Vorstlaan/Boulevard du Souverain 36, 1170 Brussels, Belgium, Tel: (32) 2 663 0600, Fax: (32) 2 663 0640

Asia Pacific: Rockwell Automation, Level 14, Core F, Cyberport 3, 100 Cyberport Road, Hong Kong, Tel: (852) 2887 4788, Fax: (852) 2508 1846